



June Tailor, Inc.

Sew-In Colorfast Fabric™ Sheets Instructions

- Design your image on the computer using your own photos, graphics or text.
- If desired, test print your image on a plain sheet of paper.
- Load one Colorfast Fabric™ sheet into printer so printing will appear on the unmarked, fabric side of the sheet.
- Printer should be set at normal quality, plain paper setting. Print image.
- Allow ink to dry at least 10 minutes. Remove paper backing from fabric.
- Set iron to highest (cotton) setting. NO STEAM. Iron image, face up, for 1 to 2 minutes to set ink. Caution: Do not use excessive pressure to iron image as fabric may distort.
- Colorfast treatment: Rinse gently in cold water. Lay flat to dry. Dab excess water with clean paper towel. Do not rub! Iron at highest setting, no steam to finish drying fabric. Caution: Do not use excessive pressure to iron image as fabric may distort.
- Sew your newly created fabric sheet into your project.

Laundering:

Printed sheets can be washed by hand or machine in cold water if Colorfast treatment was done. Do not use detergent. If machine washing, use gentle cycle. Remove promptly. If soiled, add a small amount of liquid fabric softener to cold water wash. Lay flat to dry.

This product is intended for use in standard ink jet printers only. Do not use in other printers or copiers such as laser printers or any other printer/copier that applies heat, as it may damage the machine. Test the product you plan to use to determine the suitability of the product for your equipment, methods and substrate material.