



June Tailor, Inc.

# *Jean Trix™ Inkjet Printable Iron-On Sheet Instructions*

## **1. MATERIALS NEEDED**

- Jean Trix™ Inkjet Printable Iron-On Sheet
- Computer and inkjet printer
- Garment or other project on which to apply design image.
- Ordinary household hand iron
- Pillowcase
- Smooth, hard, heat resistant surface, such as a wood cutting board for ironing. Do not use ironing board, glass or heat sensitive surfaces.

## **2. CREATE YOUR IMAGE**

- Design your image on the computer. - OR -
- If you would like to select an image from the June Tailor® Image Library, go to [www.junetailor.com](http://www.junetailor.com), click "Creativity Center" on the left side of your screen, and click on "Image Library".
- Click on desired image and wait for larger version to open.
- Right click on desired image.
- Select "Save Picture As" option to file in "My Documents" (or browse to desired location and save). - OR - Select "Copy" option, navigate to an open program such as Microsoft Word\* or any compatible jpeg image editing program, and paste.
- To size image as desired, open image in appropriate program, click and drag image corner to enlarge or reduce (or use the proper program tool for resizing).

NOTE: Black or very dark ink colors work best as inkjet printer inks are transparent allowing the Jean Trix™ fabric to show through.

## **3. PRINT YOUR IMAGE**

- It is suggested that you print a test page on plain paper prior to printing on the Jean Trix™ Sheet.
- Load one Jean Trix™ Inkjet Printable Iron-On Sheet into printer so printing will appear on fabric side of sheet.
- Print image using plain paper setting.
- Allow ink to dry.
- Trim around image if desired.

## **4. IRON YOUR IMAGE**

- Preheat iron to medium/high to high setting. **DO NOT USE STEAM.**
- Place pillowcase on smooth, hard, heat resistant ironing surface. Do not use ironing board. Iron pillowcase, if necessary, to remove wrinkles. Place garment or project on pillowcase and iron to remove wrinkles.
- Position design image as desired face up on project surface.
- Press entire image for 10 to 15 seconds. When design image is larger than iron, make sure the entire image, including edges, receives a full 10 to 15 seconds of pressing time to be thoroughly fused.

## **5. WASHING INSTRUCTIONS**

- Wash by hand in cold water. If soiled, use a small amount of liquid softener in water. Do not use detergent.
- Lay flat to dry.